



Plywood & Composite Sheets

Construction Plywoods

Many contractors shop at Windsor Plywood for their exterior sheathings and construction materials. Windsor Plywood carries a complete selection of sheathings in Fir and Spruce in thicknesses including 3/8", 1/2", 5/8", and 3/4". Both the 5/8" and 3/4" thickness are available in "tongue-in-groove" style for flooring and decking applications. In addition to roof, wall and floor sheathing, our exterior plywoods are also used for any construction use where sanded material or uniform surfaces are not required.



OSB (Oriented Strand Board)

Rigid and dimensionally stable and very strong. Cuts and nails easily and approved for exterior sheathing.

Select T & G Softwoods

Perfect for decking, floors or roofs. Available in 5/8" & 3/4" thickness in Spruce, Fir and OSB. Sanded and unsanded.

Duratemp Siding Plywood

Grooved on 8" centers. Available in a variety of sizes and thicknesses. Resawn look designed to look like siding.



Recycled Plastic Sheetting

A flexible and extremely durable product available in gray or off white and in thicknesses from 1/4" to 3/4" in 4' x 8' sheets.

- Waterproof: never swells, buckles or deteriorates underwater
- Damp-proof: resists moisture from air
- Leakage-proof: it never leaks through the solid body
- Decay-proof: never rots in open air, water or underground
- Soundproof: provides excellent sound insulation
- Corrosion-resistant: never corrodes in sea water, thinner, alkalis or acids
- Freeze - Thaw Resistant: never becomes brittle
- UV Resistant: resists ultraviolet rays deterioration
- Forklift Ramming Resistant: withstands heavy impact & scuffs
- Maintenance Free