

Windsor Plywood

NATUR CORK

FLOORING TIP GUIDE



PRE-INSTALLATION NOTES

- Store the material flat in the unopened packages for 48 hours at room temperature 64⁰F (18⁰C) prior to installation.
- Before installing the material, inspect all panels for flaws.
- Natur Cork flooring is laid floating, i.e. only the tongue and grooves are interlocked, both lengthwise and crosswise.
- Integrated cork backing, the use of any underlay, ex. (foam) is not required on the subfloor.

FEATURES & BENEFITS

- Thermal and acoustic properties
- Natural product
- Residential or commercial application
- 100% pure CORK top and bottom layer

PRE-VARNISHED CORK MODELS

- Under normal usage, no additional finishing is required for Natur Cork flooring.
- But in the case it is deemed necessary to further protect the seems against water infiltration or humidity, Another coat of varnish may be applied to the flooring 48 hours following the installation.
- Use a high quality hardwood flooring water-based or oil-based polyurethane varnish.

IMPORTANT TIP!

- It is recommended that the flooring be cleaned using a floor cleaning solution

TECHNICAL DATA

Panel Size	35 11/16" x 11 13/16" x 7/16"
Panels per box	6 Panels
Coverage per box	17.44 Square feet

The *experts* you need to know!

Windsor Plywood