

ENGINEERED HARDWOOD FLOORING

Kährs

QUALITY IN WOOD SINCE 1857



KAHR'S WOOD FLOATING FLOOR

Why Buy a Kährs Real Wood Floor?

Dimensionally stable multi-layer cross grain construction resists seasonal expansion and contraction. Can be installed from the basement to attic, over wood, concrete or radiant heat floors.

- Sandable at least 2 times
- Easily recoatable
- Install on or below grade
- Lifetime structural warranty
- No gapping of boards
- Install over radiant heat
- Quick "no odor" installation
- Square edge installation
- Board damage is replaceable
- Wide board available
- Immediate use after installation
- Dust free factory finish
- Environmental certification



THE FINISH

1. The four to six layers of Kährs UV-cured acrylic finish or UV oil is factory applied and ready to be walked on as soon as the floor is installed.

THE TOP LAYER

2. The top layer of the hardwood is available in many different wood species and patterns.

THE SUPPORT LAYER

3. A supporting layer guarantees stability and shape retention.

THE BASE LAYER

4. This products have a backing of spruce, giving added shape retention to these floors that can be installed by the float-in method.

WOODLOC® JOINT

Most of our floors come with the revolutionary joint system - woodloc®, for easy laying and perfect results

**The *experts* you
need to know!**

Windsor Plywood